

AG1020 Analog Multi-Tester With Side Attachable Test Leads

Features:

- 16 ranges with 6 functions
- DC Voltage measurement up to 500V
- AC Voltage measurement up to 500V
- DC Current measurement up to 250mA
- Resistance measurement up to 2M Ω
- Decibel Reading -10 to 56dB
- Fast Acting Fuse Protected
- Protective Holster
- Conform to IEC1010/EN61010, CE-EMC & LVD



Accessories:

- User's manual
- Test lead
- Holster

Battery required:

- 1.5V battery
(Not included in accessories)

GENERAL SPECIFICATION

Power	Single, standard 1.5 volt battery AA
Dimension	150 (L) x 90(W) x 35 (D) mm
Net Weight	Approx. 290 g (including battery and packaging)

Due to our policy of continual product development we reserve the right to amend the specifications of all mentioned products without notice.

TECHNICAL SPECIFICATION

Accuracies are \pm (% of reading + number of least significant digits), at 23 \pm 5°C, less than 75%RH

DC Voltage	Range	Sensitivity	Accuracy
	0 – 2.5V	2k Ω /V	\pm (5% full range)
	10V		
	50V		
	250V		
	500V		

AC Voltage	Range	Sensitivity	Accuracy
	10V	9k Ω /V	\pm (5% full range)
	50V		
	500V		

Internal resistance: 9k Ω /V

DC Current	Range	Accuracy
	0- 0.5mA	\pm (5% full range)
	10mA	
	250mA	

Resistance	Range	Accuracy
	0 – 2k Ω	\pm (3% of arc) arc length 62,5mm
	2M Ω	

Battery Test	Range	Test current
	1,5V	110mA
	9V	9mA



BST Caltek Industrial Ltd.

www.bstcaltek.com

www.caltek.com.hk

www.htcaltek.com

www.finestcaltek.asia

Flat G, 2/F., Block 4, Golden Dragon Industrial Centre, 182-190 Tai Lin Pai Road, Kwai Chung, N.T., Hong Kong

E-MAIL: sales@caltek.com.hk

TEL: (852) 2401-1222

FAX: (852) 2420-3472

Due to our policy of continual product development we reserve the right to amend the specifications of all mentioned products without notice.